



ANC-4130 3m Antenna Cable, N Male Plug to N Female Jack

Product Images



Short Description

1. VSWR: 1000~2000MHZ ≤ 1.2 , 3000~6000MHZ ≤ 1.5
2. Conductor Outside Diameter: 2.74 ± 0.03 mm
3. Insulator Outside Diameter: 7.24 ± 0.15 mm

4. Jacket Outside Diameter: 10.3±0.2mm
5. Insulation Resistance: 1000↑MΩ/Km
6. Conductor Composition: 1/2.74mm
7. Shield Composition: 24*7/0.16mm
8. Shield Outside Diameter: 7.92mm
9. Conductor Resistance: 4.6↓Ω/Km
10. Shield Composition: 0.038mm
11. Insulator Thickness: 2.3mm
12. Frequency Range: DC~6GHz
13. Jacket Thickness: 1.2mm
14. Capacitance: 79±3 PF/M
15. Conductor AWG: 17
16. Spark Test: 3000V
17. Impedance: 50±3Ω

Description

DDC 400 Series cable assemblies are manufactured from the highest performance Low Loss cable. It is the preferred cable for distances greater than 3m, and has become the "standard" for all outdoor antenna cabling. Weatherability DDC 400 series cables are designed for outdoor exposure incorporates the best materials for UV resistance and have life expectancy of more than 10 years.

Additional Information

Product weight (kg)	0.5
Product breadth (mm)	3000
Product height (mm)	10.3
Color	Black
EAN	4015867149249
Model number	ANC-4130
Package contents	ANC-4130

